

## **Teknisk info**

### **Exemplary configuration**

#### **Configuration example 1:**



**Inkl. mounting frame and cover.**

#### **Casing:**

**For 2 modules. The modules and also the body are in black.**

#### **Power supply:**

**Starter cable with angled Schuko-/BE-plug (16 A), cable length app. 2900 mm. NO power Output.**

#### **Wiring:**

**1,5 mm<sup>2</sup>**

**Fitting:**

**1 x Schuko-enhanced contact protection (vertical)**

**1 x USB-charging-unit. 2 x female USB-connector Type A, max. output current: 2.1 A, 5 V DC (10.5 VA)**

**Configuration example 2:**



**Inkl. mounting frame and cover.**

**Casing:**

**For 2 modules. The modules and also the body are in black.**

**Power supply:**

**Starter cable with angled Schuko-/BE-plug (16 A), cable length app. 2900 mm. NO power output.**

**Wiring:**

**1,5 mm<sup>2</sup>**

**Fitting:**  
**2 x BEK (diagonal)**

**Configuration example 3:**



**Inkl. mounting frame and cover.**

**Casing:**  
**For 2 modules. The modules and also the body are in black.**

**Power supply:**  
**Starter cable with GB-plug (13 A), cable length app. 2900 mm. NO power output.**

**Wiring:**  
**1,5 mm<sup>2</sup>**

**Fitting:**  
**2 x GB-Y fused @ 3,15 Amps (vertical)**